



FORKLIFT

LG35DT
LG50DT

CATALOGUE

 **RONDEBULT**
CONSTRUCTION MACHINES

Head Office South Africa:

2 Tungsten Street, Ekandustria,
Bronkhorstspuit, South Africa.

Tel: +27 13 933 3643,

Fax: +27 13 933 3644.

Email: sales@rondebult.co.za

www.rondebult.co.za



POWERFUL ENGINE WITH
ADVANCED WIRING HARNESS
& WATERPROOF PARTS

FORKLIFT

LG35DT/LG50DT

Model	LG35DT	LG50DT
Power type	Diesel	Diesel
Rated Capacity (kg)	3500	6000
STD Engine	Xinchai A495BPG	Chaochai CY6102BG
Rated Power	40kW	81kW
J Load centre (mm)	500	600
h1 STD Max lifting height (mm)	3000	3000
h3 Free lift height (mm)	188	200
L5*W*T STD Fork size (mm)	1070*125*50	1220*150*60
Mast tilt angle (deg)	6/12	6/12
L3 Front overhang (mm)	493	589
L4 Rear overhang (mm)	525	695
Overall dimension		
L1 Overall length (with fork) (mm)	3788	4754
W1 Overall width (mm)	1225	2000
h2 Mast lowered height (mm)	2177	2500
h4 Overhead guard height (mm)	2100	2480
R1 Min. turning radius (mm0)	2450	3415
Min. Intersecting aisle (mm)	4155	5610
Speed (load/unload)		
Max. travelling speed (mm/s)	19/20	24/25
Max. lifting speed (mm/s)	430/450	330/450
Max. gradient (%)	20	20
Self weight (kg)	4650 (4700)	9100
S/P Tread (front/rear) (mm)	1000/980	1470/1700
L2 Axle distance (mm)	1700	2250
Min.ground clearance		
m2 Mast (mm)	132	201
m1 Frame (mm)	147	248